

WhiteboardMatt ASLAN WB 975

High quality, matt whiteboard film

The self-adhesive, matt whiteboard film is ideally suitable for often changing writings in schools, seminar rooms, kindergartens, hospitals and many places more. The highly scratch-resistant surface avoids any shadows or ghostings. Writings can be wiped off easily with a microfiber cloth.

The non-reflective, matt surface of the film is perfectly designed for front projections.

For any further information please contact our technical advisory service:
+49 (0)2204.708-80

Construction

face-film:	Soft PVC, white matt with special lacquering	
thickness:	~ 80 µm	
adhesive:	acrylic pressure sensitive adhesive	thickness: ~ 25 g/m ²
release liner:	silicone cardboard	square weight: ~ 144 g/m ²

Characteristics

adhesive strength: (ASTMD-903)	immediately after 1 week	~ 8 N/25 mm ~ 10 N/25 mm
dimensional stability:	applied onto aluminum after 48 hours stored at 70 °C (25 x 25 cm)	max. -0.2 %
chemical resistance:	In a preece test of 24 hours the applied film is resistant to most petroleum based oils, greases and aliphatic solvents, mild acids, alkaline and salts.	
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C

ASLAN, Schwarz GmbH & Co. KG
Postfach 5165 · 51486 Overath · Oberauel 2 · 51491 Overath
fon +49 (0) 2204.708-80 · **fax** +49 (0) 2204.708-50 ·
e-mail info@ASLAN-schwarz.com

www.ASLAN-schwarz.com

ASLAN 
EXPERTISE IN SELF-ADHESIVE FILMS

WhiteboardMatt ASLAN WB 975

Processing

application:	The film can be applied dry or wet. A possible whitening of the adhesive if applied wet will disappear after a few days' time, depending on the weather conditions. For wet applications we recommend our transfer liquid ASLAN TL 10.
Usage	For writings on the film any customary whiteboard marker can be used. For an easy cleaning a microfiber cloth must be used. Writings with non-suitable pens (i.e. permanent markers) can be removed with alcohol or white gas.
storage life:	Before application the films can be stored at least 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

State: 09|2013

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG
Postfach 5165 · 51486 Overath · Oberauel 2 · 51491 Overath
fon +49 (0) 2204.708-80 · **fax** +49 (0) 2204.708-50 ·
e-mail info@ASLAN-schwarz.com

www.ASLAN-schwarz.com

ASLAN® 
EXPERTISE IN SELF-ADHESIVE FILMS